



CHECK VALVE - INLINE - CUT



- 7 SIZES - FLOWS TO 270 LPM
- MAX.WORKING PRESSURE - 200 BAR
- CHOICE OF CRACKING PRESSURE .35 / 3.5 BAR
- STEEL POPPET TYPE CONSTRUCTION
- PREVENTS FLOW IN REVERSE DIRECTION
- SUITED FOR MINERAL / PETROLEUM BASED OILS
- NOT RECOMMENDED FOR USE TO CHECK REVERSE FLOW



MODEL NO	THREADED SIZE IN. BSPP	RATED FLOW LPM	A MM	'B' A/F MM	WT KGS
CUT . 02 . 5	1/4"	20	65	19	0 . 15
CUT . 03 . 5	3/8"	30	75	25	0 . 25
CUT . 04 . 5	1/2"	50	85	30	0 . 40
CUT . 06 . 5	3/4"	80	100	38	0 . 75
CUT . 08 . 5	1"	150	115	41	0 . 90
CUT . 10 . 5	1 - 1/4"	200	130	55	1 . 75
CUT . 12 . 5	1 - 1/2"	270	132	65	2 . 70

MODEL CODE

CUT	- 02	- 05	* *
SERIES	SIZE IN BSPP	CRACKING PR.	FEATURE OPTIONAL #
CUT	02 - 1/4" BSPP	05 - 5 PSI (STD) 50 - 50 PSI	
	03 - 3/8" BSPP		
	04 - 1/2" BSPP		
	06 - 3/4" BSPP		
	08 - 1" BSPP		
	10 - 1 - 1/4" BSPP		
	12 - 1 - 1/2" BSPP		

OPTIONAL / SPECIAL FEATURE - OMIT IF NOT REQUIRED